Life Is On





Suitable for Heat Pumps, Heat Recovery Units, Process and Industrial Chillers, Air Handling Units, Pumping and more

Free Optima

The powerful PLC for compact machines





Low-GWP gas ready

Conform to EN/IEC 60335-2-40 related to A3 refrigerants, such as R290 Suitable for A2L

Small dimensions

4-DIN module in three versions

Green Premium product

Sustainable performance, by Design Compliance with environmental regulations

1MB to support simple and complex programs

Less is more

Insulation everywhere simplifying machine wiring diagram and reducing the number of components

Adaptive

One unit for super compact machines; for bigger ones, just add I/O expansions



Flexible & Configurable

22 IOs to adapt to different machines

Inputs: NTC, PT1000, 0..5V, 0..10V, 4..20mA, voltage free, Pulse counter

Outputs: Relay, SSR, PWM, 1..10V, 4...20mA

Integrated EEVD

Integrated Unipolar Electronic Expansion valve driver

Ready-to-use assets

simplifying programming IEC61131 - Many templates, libraries, function blocks available

Multiple connection capabilities

to the other devices inside the machine Modbus RTU client and server, CANopen, USB-C, Remote display bus

IoT on deck

Straightforward connection to the Secure Interface: cybersecure IoT module

Codes	Description
OTDM22R	Free Optima, display, 22 IOs, 24 Vac/dc, 2 x RS485
OTDM22S	Free Optima, display, 22 IOs, 24 Vac/dc, 2 x RS485, 2 x SSR
OTBM22R	Free Optima, 22 IOs, 24 Vac/dc, 2 x RS485

Digitization

ITALY - Headquarters

Eliwell Controls srl

Via dell'Industria, 15 Z.I. Paludi 32016 Alpago (BL) - ITALY T: +39 0437 986 111

F: +39 0437 989 066

Sales

T: +39 0437 986 100 (Italy)

T: +39 0437 986 200 (other countries)

E: saleseliwell@se.com

Technical support

T: +39 0437 986 250

E: techsuppeliwell@se.com

CT123451 • Flyer Free Optima • EN • REL 0923 © Eliwell Controls s.r.l. 2023 - All rights reserved







