

Life Is On

eliwell™
by Schneider Electric

FREE Way

The programmable platform



www.elowell.com



FREE Way

The programmable platform



General description

The Eliwell programmable platform

FREE Way is the range of logic controllers developed by Eliwell, which consists of the **FREE Smart**, **FREE Panel**, **FREE Advance** and **FREE Evolution**.

FREE Studio Plus is the universal programming software for machines automated by the **FREE Way** logic controllers. It simplifies each of the steps in machine design and commissioning:

- 1 Unique, simple and flexible software suite software for the entire **FREE Way** range
- Compatible with the 5 standard programming languages (IEC 61131-3) to cover all needs with graphic or text languages
- Advanced debug and simulation options plus complete and effective online Help
- Tools for easy commissioning
- Advanced communication features such as remote control and download
- Webpage creation from the software

Features

FREE Smart

- User interface with configurable keys
- Available in three sizes, in the 100...240Vac and 12...24 Vac/ 24Vdc versions:
 - **FREE Smart SMP**, panel mount (32x74mm) with LED display
 - **FREE Smart SMD** 4 DIN with LED display, **FREE Smart SMC** 4 DIN blind
- Connectible via RS-485, Modbus RTU or Eliwell standard user interfaces and peripherals

FREE Panel

- Available in two sizes:
 - **FREE Panel EVP** system controller, with gateway functions and monochrome backlit LCD display, available for panel mounting (**FREE Panel EVP**) or wall mounting
 - **FREE Panel AVP** one controller with backlit colour graphic touch display, for wall or panel mounting, with built-in temperature, humidity and presence sensors
- High connectivity: can be integrated in industrial systems and micro BMS
- Connectible with Eliwell standard and third-party peripherals

FREE Advance

- Fully customizable graphic user interface
- Available in 4 Din and 8 Din sizes, **FREE Advance AVD** with backlit LCD graphic display, **FREE Advance AVC** blind
- High built-in connectivity as standard for integration in industrial systems and BMS
- Connects to standard Eliwell peripheral devices (including FREE Smart) to any network whatever it is Modbus SL, BACnet MS/TP, Modbus TCP, BACnet IP or LonWorks network
- A slot for a micro SD memory card that can be used for data logging or Webserver storage
- USB programming ports

FREE Evolution

- Fully customizable graphic user interface
- Available in 8 Din FREE Evolution EVD sizes with backlit LCD graphic display and **FREE Evolution AVC** blind versions
- High connectivity: integrates into industrial systems and BMS using dedicated plug-in modules which allows to connect to BACnet MS/TP, Modbus TCP and BACnet IP networks
- Connects to standard Eliwell peripheral devices (including FREE Smart) and third party devices
- USB programming ports

Certification c^{UL}us depending on model, specified in UL reference file no. E233482

AVP1100/1200/1300: CTUVus certification indicated in UL reference file no. U8 17 05 54090 001

Plus points



FREE Panel AVP

Speed

One of the FREE programmable platform's main aims is to enable customers to create solutions for their customers fast. Many FREE features significantly cut the times between design of a new application and its production release.

Compactness

The FREE programmable platform makes customers cost-competitive. FREE controllers were designed with a strong focus on technology and physical size, with impressive results in terms of simplicity, modularity and compactness. FREE controllers' integrated solutions and small size generate real, immediate financial savings for customers.

Efficiency

Complete and scalable to different complexity levels, the FREE programmable platform gives customers great freedom to choose the solution they consider best for their application. This allows easy identification of solutions that cut costs or item numbers, facilitating solutions more open to future developments or future system demands, especially with regard to connectivity.

Reliability

The FREE Way programmable platform's high quality standards enable customs to save on the costs generated by quality nonconformities both in their production processes and in installations in the field. **FREE Smart**, **FREE Panel**, **FREE Advance** and **FREE Evolution** controllers and the **FREE Studio Plus** development environment were all designed with innovative but carefully defined criteria, using state-of-the-art yet stable technology solutions and certified, monitored production processes. Eliwell has always been famed for its reliability.



FREE Advance



FREE Evolution



FREE Smart

The FREE Way targets

Constructors of:

- AHUs (Air Handling Units)
- Chillers
- Heat Pumps
- Rooftop Units
- Precision air-conditioners
- Compressor Rooms

Installers/system integrators of:

- All-air systems
- Hydronic systems
- Air-water systems
- Commercial automation

FREE Studio Plus

The **FREE Studio Plus** software suite is compatible with all 5 standard programming languages (**IEC61131-3**). Every project may comprise several programs; developers can use more than one language in the same project.

Every new program has a choice of 5 programming languages, 2 textual and 3 visual:

- **ST, Structured Text**
- **FBD, Functional Block Diagram**
- **LD, Ladder**
- **IL, Instruction List**
- **SFC, Sequential Function Chart**

IEC61131-3 development software

Main functions

Variable display with application running

Debugging of variables through display of their status in numerical format when the application is running and connected to FREE Smart, FREE Panel, FREE Advance and FREE Evolution

Function Library

Management of default and/or developer-created function libraries.

Any additional cards are managed by the developer himself

Variable graphic display

Debugging of variables through display of their status in graphic format when the application is running and connected to FREE Smart, FREE Panel, FREE Advance and FREE Evolution

Variable reading / writing

The working environment allows:

- creation of a dedicated menu to be shown on the device's display
- reading and writing of BIOS parameters (parameters + I/O values)
- reading and writing of the parameters and variables defined by the developer in Applications associated to the menu

On-line Help to assist the programmer in every program development phase, accessed from the context by just pressing the F1 button.


The whole on-line help guide is also available in printable pdf format

Baselines and Libraries, ready to use and available for download via web


```
var2:=var2+1;
if var2>20 then
var2:=0;
var1:=not var1;
counter:=counter+1;
if (DP=TRUE) then
out1:=counter and 5;
out2:=counter and 7;
out3:=counter and 12;
else

```

ST




FBD




LD

```
Id true
st init.run
Id true
st blinker.run
cal trigger
```

IL



SFC



Components

FREE Studio Plus is the universal programming software for machines automated by the **FREE Way** logic controllers. It simplifies each of the steps in machine design and commissioning:

FREE Studio Plus allows developers to program in various working environments, since they can access constantly updated with new functions and optimizations, available in the specific area of the Eliwell web site.

- 1 Unique, simple and flexible software suite software or the entire **FREE Way** range
- Compatible with the 5 standard programming languages (IEC 61131-3) to cover all needs with graphic or text languages
- Advanced debug and simulation options plus complete and effective online Help
- Tools for easy commissioning
- Advanced communication features such as remote control and download
- Webpage creation from the software
- Advanced communication features as remote control and download
- Webpage creation for the software



Baselines

Applications supplied ready to use, compliant with architecture rules, easily modified to all requirements.

Libraries of objects to save you even more time, by making FREE Studio Plus easier to use.

System and installation requirements

Operating Systems

- Windows 10 English
- Windows 8, 8.1 English
- Windows 7 Home / Professional / Ultimate English

Supported browser

- Internet Explorer 11 or greater

The installation setup, software updates, libraries and documentation are available on the elowell.com website, after registration for access to the private area.

FREE Smart models

Models are available both DIN rail mount version (SMD with display, SMC without display) and in the 32x74 Eliwell standard version (SMP) panel mount version.

The offering is completed by various expansions (SME) and terminals (SKP, SKW) for combination with FREE Smart series models.

All inputs and outputs are independent and configurable to ensure adaptability to any system.



FREE Smart 12...24 Vac / 24Vdc /C identifies units with RTC – Real Time Clock

Model	Code	Digital Outputs at hazardous voltage	TRIAC Outputs at hazardous voltage	O.C. outputs: PWM / PPM at safety extra low voltage (SELV)	Analog outputs 0-10 V at safety extra low voltage (SELV)	Digital Inputs voltage free	Analogue Inputs at safety extra low voltage (SELV)	O.C. Outputs	RS 485 built-in
SMP5500/C/S	SMP5500050450	5	-	2	3	6	5	1	yes
SMP5500/C	SMP5500010450	5	-	2	3	6	5	1	-
SMD5500/C/S	SMD5500050450	5	-	2	3	6	5	1	yes
SMD5500/C	SMD5500010450	5	-	2	3	6	5	1	-
SMD3600/C/S	SMD3600050450	3	2	1	3	6	5	1	yes
SMC5500/C/S	SMC5500050450	5	-	2	3	6	5	1	yes
SMC5500/C	SMC5500010450	5	-	2	3	6	5	1	-

Expansions

SME3200	SME3200000400	3	-	2	-	6	3	1	-
SME5500	SME5500000450	5	-	2	3	6	5	1	-

FREE Smart 100...240 Vac /C identifies units with RTC – Real Time Clock/S identifies units with built-in RS485 serial output

Model	Code	Digital Outputs at hazardous voltage	O.C. outputs: PWM / DI at safety extra low voltage (SELV)	Outputs 0...10 V at safety extra low voltage (SELV)	Outputs 4...20 mA / 0...20 mA	Analog inputs at safety extra low voltage (SELV)
SMD4500/C/S	SMD4500050H00	4	2	2	1	5
SMD4500/C	SMD4500010H00	4	2	2	1	5
SMC4500/C/S	SMC4500050H00	4	2	2	1	5

Expansion

SME4500	SME4500000H00	4	2	2	1	5
----------------	---------------	---	---	---	---	---

Terminals with power supply from base

Model	Code	Mount	Dimensions	Display	Analog inputs at safety extra low voltage (SELV)
SKP10	SKP100G000000	panel	74x32x30 mm	LED / 4 digits	-
SKW22	SKW220G000000	wall	137x96.5x31.3 mm	LCD	1 built-in NTC 1 NTC input / DI / 4...20 mA
SKW22L	SKW22LG000000	wall	137x96.5x31.3 mm	Backlit LCD	1 built-in NTC 1 NTC input / DI / 4...20 mA
SKP22	SKP220G000000	panel; wall: see Accessories page	160x96x10 mm	LCD	1 NTC input 1 NTC input / DI / 4...20 mA

KEY: SELV = Safety Extra Low Voltage; PPM = Pulse Position Modulation; PWM = Pulse Width Modulation; O.C. = Open Collector

Available resources - FREE Smart (model /C/S, msk 412)

The IEC programmer has the following resources:

CPU	14.7 MHz
memory available for Application	190 Kbytes
RAM - automatic mapping	2300 Bytes
RAM - Modbus mapping	1024 Byte
EEPROM variables	1024 Byte

Minimum developer kit - FREE Smart

- FREE Studio Plus installation setup
- 1 FREE Smart SMxxxx*
- 1 DMI 100-3 Manufacturer + yellow TTL cable
- 1 MFK optional + blue TTL cable
- FREE Smart* power supply wiring and transformer

* otherwise, order the Demo Case




FREE Smart connectivity

FREE Smart controllers are equipped with a serial port for easy integration with the supervision systems of the installation plant.

All controller resources can be accessed via standard Modbus communication protocol, guaranteeing complete control of the plant.

All models have TTL port as standard; /S models have built-in RS485 serial port.

A special Firmware version also provides the Modbus MASTER function.



FREE Smart maximum configuration

- max 1 FREE Smart model
- max 1 SME expansion by LAN serial line
- max 1 SKP10 terminal with controller ECHO function
- max 1 SKW22(L) or SKP22 terminal with dedicated menu, allowing ambient temperature and humidity monitoring
- LAN maximum distance: 100 m

FREE Smart update function


Multi Function Key (MFK 100) for uploading and downloading parameter map for quick configuration, and uploading the IEC application and BIOS.

Multi Function Key / DMI PC → ← FREE		
	USB	TTL
DMI MFK		
use blue TTL cable for DMI - MFK connection	→	←
Data download direction	→	←
Parameter map	-	-
IEC application	✓	-
BIOS	✓	-


Multi Function Key MFK → ← FREE		
	TTL	
MFK FREE Smart		
use yellow TTL cable for MFK - target connection	→	←
Data download direction	→	←
Parameter map	✓	✓
IEC application	✓	-
BIOS	✓	-

Network PC → ← FREE		
	USB	TTL
FREE Studio Plus DMI FREE Smart		
use yellow TTL cable for DMI - target connection	→	←
Data download direction	→	←
Parameter map	✓	✓
IEC application	✓	-
BIOS	✓	-

Modbus Slave or Master mode connection examples



For models without RS485 use only BusAdapter 150



SMP, SMD, SMC5500



SMP5500



SMD5500





SMC5500


Technical data

	SMP5500	SMD5500	SMC5500
size	32x74x80 mm (Lxhxw)	4DIN	
display	LED 4 digit - 7 segments		-
power supply	12...24 Vac / 24 Vdc		
relay digital outputs	5 x 2 A 250 Vac		
analog outputs	2 x O.C. PPM/PWM 3 x 0...10 V		
O.C. digital outputs	1 Open Collector		
digital inputs	6 voltage free		
analog inputs	3 x NTC / D.I. 2 x NTC / D.I. / 0...20 mA / 4...20 mA / 0-10 V / 0-5 V / 0-1 V		
connectivity	TTL RS485 isolated (only /S models) LAN for connection to SKP/SKW terminal or SME expansion		
operating temperature	-20...+55 °C		


Electric, mount and dimensional diagrams



Dimensionali SMD, SMC, SME



SMP5500/C - SMP5500/S



SMD5500/C/S - SMC 5500/C - SMC5500/C/S

SMD3600, SME Expansions



SMD3600



SME3200




SME5500


Technical data

	SMD3600	SME3200	SME5500
size		4DIN	
display	LED 4 digit - 7 segments	-	-
power supply	12...24 Vac		12...24 Vac / 24 Vdc
relay digital outputs		3 x 2A 250 Vac	5 x 2A 250 Vac
analog outputs	2 x TRIAC 3 A 250 Vac 1 x Open Collector PPM/PWM 3 x 0...10 V	- 1 x Open Collector PPM/PWM -	- 1 x Open Collector PPM/PWM 3 x 0...10 V
O.C. digital outputs	2 Open Collector		1 Open Collector
digital inputs		6 voltage free	
analog inputs	3 x NTC / D.I. 2 x NTC / D.I. / 0...20 mA / 4...20 mA / 0-10 V / 0-5 V / 0-1 V	3 x NTC / D.I. -	3 x NTC / D.I. 2 x NTC / D.I. / 0...20 mA / 4...20 mA / 0-10 V / 0-5 V / 0-1 V
connectivity	TTL RS485 isolated LAN for connection to SKP/SKW terminal or SME expansion	TTL -	TTL -
operating temperature	-20...+55 °C		


Electric diagrams



SMD3600/C/S



SME3200



SME5500

SMD, SMC4500, SME4500 Expansion



SMD4500



SMC4500




SME4500


Technical data

	SMD4500	SMC4500	SME4500
size		4DIN	
display	LED 4 digit - 7 segments	-	-
power supply		100...240 Vac	
relay digital outputs		4 x 2 A 250 Vac	
analog outputs		2 x Open Collector PWM/D.I. 2 x 0...10 V 1 x 4...20 mA / 0...20 mA	
analog inputs	3 x NTC / Pt1000 / D.I. 2 x NTC / D.I. / 0...20 mA / 4...20 mA / 0-10 V / 0-5 V / 0-1 V		3 x NTC / D.I. 2 x NTC / D.I. / 0...20 mA / 4...20 mA / 0-10 V / 0-5 V / 0-1 V
connectivity	TTL RS485 LAN for connection to SKP/SKW terminal or SME expansion		TTL -
operating temperature		-20...+55 °C	

Electric diagrams



SMD4500/C/S - SMC4500/C/S



SME4500 Expansion

Interfaces, FREE Smart Terminals



SKP10



SKW22/22L




SKP22




Technical data

	SKP10	SKW22 - SKW22L	SKP22
size (LxDxH)	74x32x30 mm	4DIN	
mount	panel	wall	panel
display	LED 4 digit - 7 segments	LCD (model 22L: Backlit LCD)	LCD
power supply	from base		
analog inputs	-	1 x built-in NTC 1 x NTC / D.I. / 0...20 mA / 4...20 mA remote	1 x remote NTC 1 x NTC / D.I. / 0...20 mA / 4...20 mA remote
connectivity	LAN for connection to FREE Smart		
wiring	COLV000033200 cable included in pack		
operating temperature	-20...+55 °C	-5...+60 °C	
humidity module	-	KP100000 - not included (see Accessories page)	-



Electric and mount diagrams



SKP10



SKW22 - SWK22L



SKP22

FREE Panel models

FREE Panel AVP is the completely customizable solution for creating an easily maintained and serviced zone controller with backlit color graphic touchscreen display, mounting on vertical surfaces, Modbus Slave connectivity, and integral temperature, humidity and presence probes.

The panel version adds Modbus Master connectivity with option of installation inside a machine, also on DIN rail.

FREE Panel EVP is the version with LCD graphic display suitable for use as system controller, with gateway functions, used in association with the other FREE Advance, FREE Evolution and FREE Smart controllers or third party devices.

FREE Panel EVP delivers excellent performance in terms of memory, user interface, Master/Slave connectivity and expandability (up to 7 expansions via field CANbus), and is easy to program, maintain and service.

A special base plate is available as wall mount accessory.



FREE Panel AVP



FREE Panel EVP

FREE Panel AVP /C identifies units with RTC – Real Time Clock /P identifies panel mount

Model	Code	Mount	Display	Built-in probe	Serial
AVP1000 /P WHITE	AVP100W0P0500	panel*	color touchscreen display 3.5" 320x240	-	RS485** - Modbus SL USB Micro-B
AVP1000 /P GREY	AVP100G0P0500	panel*	color touchscreen display 3.5" 320x240	-	RS485** - Modbus SL USB Micro-B
AVP1100 /C	AVP11000W0500	wall***	color touchscreen display 3.5" 320x240	temperature	RS485** - Modbus SL USB Micro-B
AVP1200 /C	AVP12000W0500	wall***	color touchscreen display 3.5" 320x240	temperature & relative humidity	RS485** - Modbus SL USB Micro-B
AVP1300 /C	AVP13000W0500	wall***	color touchscreen display 3.5" 320x240	temperature, relative humidity and presence	RS485** - Modbus SL USB Micro-B

*both horizontal and vertical (for vertical surface mount see Accessories page)

**RS485 Master or Slave

***Vertical mount. Horizontal mount if built-in probes are not used.

FREE Panel EVP /C identifies units with RTC – Real Time Clock /RH: humidity probe

Model	Code	Mount	Display	Inputs at safety extra low voltage (SELV)	Serial
EVP3300/C	EVP3300010B00	panel*	Backlit LCD	1 x built-in NTC; 1 x remote NTC; 1 x remote 4...20 mA / 0-5 V / 0-10 V	CANbus; RS485; Ethernet
EVP3500/C/RH	EVP3500010B00	panel*	Backlit LCD	1 x built-in NTC; 1 x remote NTC 1 x built-in %RH	CANbus; RS485; Ethernet

*(for wall mount see Accessories page)

KEY: SELV = Safety Extra Low Voltage



Available resources - FREE Panel

The IEC programmer has the following resources:


	FREE PANEL AVP	FREE PANEL EVP
CPU	120 MHz, 132 kB RAM	72 MHz, 32 Mbyte RAM
memory available for Application + User Interface	736 Kbytes	1 Mbyte + 1.5 Mbyte = 2.5 Mbyte
FLASH data memory	4 Mbyte (images + font)	128 Mbyte
RAM - automatic mapping for Application + User Interface	78 Kbyte	512 Kbyte + 512 Kbyte
RAM - Modbus mapping	5000 words	5000 words
EEPROM variables	4000 words (application)	4000 words (application) + 10000 words (BACnet objects)

FREE Panel connectivity

AVP



EVP




Connectivity and functions


FREE Panel AVP delivers excellent performance in terms of memory, color user interface with resistive touchscreen display and Modbus Master/Slave connectivity, and is easy to program, maintain and service.

FREE Panel EVP delivers excellent performance in terms of memory, user interface, Master/Slave connectivity and expandability (up to 7 expansions via field CANbus), and is easy to program, maintain and service.


USB-RS485; Ethernet PC → ← FREE



USB Host PC → ← FREE



Ethernet PC → ← FREE



Data download direction	→	←
Parameter map	✓	✓
IEC application	✓	-
HMI application	✓	-
Data files	✓	✓
BIOS	✓	-
Commissioning	✓	✓

Data download direction	→	←
Parameter map	✓	✓
IEC application	✓	-
HMI application	✓	-
Data files	-	-
BIOS	✓	-

Configuration permissible with FREE Advanced in Bridge mode and AVP in Slave mode

Data download direction	→	←
Parameter map	✓	✓
IEC application	✓	-
HMI application	✓	-
Data files	-	-
BIOS	✓	-

AVP1000



AVP1000/P WHITE







AVP1000/P GREY


Technical data

	AVP1000/P WHITE	AVP1000/P GREY
size	134x96x35 mm	
enclosure rating	IP 65 on front panel	
display	color touchscreen display 3.5" 320x240	
power supply	24 Vac/dc (Type T 500 mA UL recognized fuse)	
analog inputs	none	
connectivity	RS 485 – Modbus SL USB Micro-B (programming and debug)	
operating temperature	-20...60 °C	

Dimensional and mount diagrams



DIN rail mount



Wall mount

AVP1100, AVP1200, AVP1300



AVP1100/C



AVP1200/C





AVP1300/C

Technical data

	AVP1100/C	AVP1200/C	AVP1300/C
size		120x86x25 mm	
display		color touchscreen display 3.5" 320x240	
power supply		24 Vac/dc	
analog inputs	1 x built-in NTC	1 x built-in NTC 1 x built-in %RH	1 x built-in NTC 1 x built-in %RH 1 x built-in PIR (presence probe)
connectivity		RS485 - Modbus SL USB Micro-B (programming and debug)	
operating temperature		0...+50 °C	

Electric and mount diagrams



EVP3300/C, EVP3500/C/RH



EVP3300/C




EVP3300/C/RH

Technical data

	EVP3300/C	EVP3500/C/RH
size	160x96x10 mm	
display	backlit LCD 128x64 px graphic display	
power supply	24 Vac/dc - 48 Vdc isolated	
analog inputs	AI1 1 x built-in NTC AI2 1 x remote NTC / D.I. AI3 1 x remote 4...20 mA / 0-5 V / 0-10 V	AI1 1 x built-in NTC AI2 1 x remote NTC / D.I. AI4 1 x built-in %RH
connectivity	CANBus isolated: CANopen RS485 isolated: Modbus RTU, BACnet MSTP Ethernet: Modbus TCP - BACnet IP - WebServer	
operating temperature	-5...+55 °C	

Electric and mount diagrams



EVP3300/C - EVP3300/C/RH

FREE Advance models



FREE Advance

FREE Advance models (**AVD** with display, **AVC** without display) are available in versions for assembly on 8 DIN rail, with disconnectable screw terminal blocks for quick, easy installation.

Every AVD or AVC is expandable via CANbus (field) up to 7 expansions and 2 terminals (EVK). Up to 10 controllers can also be connected together via CANbus (network).

Up to 127 devices can be controlled with Modbus Master, via RS485.

FREE Advance with or without display /C indicates units with RTC – Real Time Clock; built-in RS485 and CANbus as standard

Model	Code		Relay outputs at hazardous voltage	SSR outputs	Analog outputs at safety extra low voltage (SELV)	Digital inputs (SELV) 2 fast pulse/frequency counters up to 2 Khz included	Analog inputs at safety extra low voltage (SELV)
AVD3000/C/L/U	AVD3000060500	Isolated	3	-	-	2	2
AVC3000/C/L/U	AVC3000060500	Isolated	3	-	-	2	2
AVD6200/C	AVD6200050500	Isolated	6	-	2	2	8
AVC6200/C	AVC6200050500	Isolated	6	-	2	2	8
AVD6200/C/L/U	AVD6200060500	Isolated	6	-	2	2	8
AVD6200/C/L/U/SSR	AVD62SS060500	Isolated	4	2	2	2	8
AVC6200/C/L/U	AVC6200060500	Isolated	6	-	2	2	8
AVC8400/C/L/U	AVC8400060500		8	-	4	8	8
AVD8400/C/L/U	AVD8400060500		8	-	4	8	8
AVD8400/C/L/U/SSR	AVD84SS060500		6	2	4	8	8
AVC12600/C/L/U	AVC1260060500		12	-	6	12	12
AVD12600/C/L/U	AVD1260060500		12	-	6	12	12
AVD12600/C/L/U/SSR	AVD126S060500		10	2	6	12	12
AVC8400/C/L/U/I	AVC840006I500	Isolated	8	-	4	8	8
AVD8400/C/L/U/I	AVD840006I500	Isolated	8	-	4	8	8
AVD8400/C/L/U/SSR/I	AVD840006I500	Isolated	6	2	4	8	8
AVC12600/C/L/U/I	AVC126006I500	Isolated	12	-	6	12	12
AVD12600/C/L/U/I	AVD126006I500	Isolated	12	-	6	12	12
AVD12600/C/L/U/SSR/I	AVD126006I500	Isolated	10	2	6	12	12
AVC8400/C/I	AVC840005I500	Isolated	8	-	4	8	8
AVD8400/C/I	AVD840005I500	Isolated	8	-	4	8	8
AVC12600/C/I	AVC126005I500	Isolated	12	-	6	12	12
AVD12600/C/I	AVD126005I500	Isolated	12	-	6	12	12

Expansions RS485 (EVE7500 only) and built-in CANbus as standard

Model	Code	Relay outputs at hazardous voltage	SSR outputs	Analog outputs (SELV) AO4/AO5 configurable as Open Collector 12 Vdc 100 mA max each	Digital inputs at safety extra low voltage (SELV)	Digital inputs voltage free	Analog inputs at safety extra low voltage (SELV)
EVE10200	EVE1020000500	10	-	2 (AO1/AO2 30 mA)	4+2**	-	10
EVE4200	EVE4200000500	4	-	2 (AO1/AO2 30 mA)	4	-	4

FREE Advance controllers are compatible also with EVE7500

*fast pulse/frequency counter 1 KHz

**fast pulse/frequency counter 2 KHz

Minimum developer kit


- FREE Studio Plus installation setup
- 1 FREE Advance AVD8400/C/L/U
- Mini USB cable for connection to PC
- Ethernet cable for network connection
- FREE Advance power supply transformer

Available resources: The IEC programmer has the following resources:

CPU	120 MHz 16 MByte RAM	RAM - automatic mapping for Application and User Interface	512 kByte + 512 kByte
memory available for Application	1 MByte	RAM - Modbus mapping	5000 words
memory available for User Interface	1.5 MByte	EEPROM variables	4000 words (application) + 10000 words (BACnet objects)
FLASH data memory	6 MByte		

FREE Advance connectivity

FREE Advance models are equipped with ETHERNET and RS-485 serial ports and built-in CANBUS as standard. They can also be integrated in industrial systems and BMS via the range of plug-in units, 2DIN modules quickly and easily connected to the AVD/AVC module.



Connectivity and functions

FREE Advance controllers feature integrated advanced functions, since they incorporate the Ethernet, BACnet, FTP and SNTP protocols as standard, as well as the LON protocol via an optional plug-in.

The Internet connection and integral WebServer offer machine constructors and system integrators complete remote access, drastically reducing service and maintenance times.

This also benefits end users, who can control their plants from multiple devices.

- Integral WebServer
- Local and remote plant control, including email alarm and alert management
- Remote reading and assistance
- Preventive and predictive maintenance
- State-of-the-art plant interface on PC, Tablet and Smartphone

SD card Datalogging SD card → ← FREE




Data download direction	→	←
Parameter map	-	-
IEC application		
HMI application	✓	
Data files		
BIOS	-	-

USB Host PC → ← FREE



Data download direction	→	←
Parameter map	✓	✓
IEC application	✓	✓
HMI application	✓	✓
Data files	✓	✓
BIOS	✓	-

Ethernet / USB Device / RS485 PC → ← FREE



Data download direction	→	←
Parameter map	✓	✓
IEC application	✓	-
HMI application	✓	-
Data files	✓	✓
BIOS	✓	-

AVD3000/C/L/U, AVC3000/C/L/U



AVD3000




AVC3000

Technical data

	AVD3000	AVC3000
size	4 DIN	-
display	backlit LCD 128x64 pixel graphic display	-
power supply	24 Vac isolated 20...38 Vdc isolated	-
digital outputs	3: 3 x 3 A 250 Vac	3: 3 x 3 A 250 Vac
digital inputs	2 x SELV can operate as pulse/frequency counters up to 2 kHz	-
analog inputs	2 x NTC 103AT / NTC NK103 / D.I. / PTC KTY81 / Pt1000 / 0...20 mA / 4...20 mA / 0-10 V / 0-5 V	-
connectivity	Ethernet: Bacnet IP, Modbus TCP Master/Slave, Webserver, Ftp Client/Server, SNTP CANBus: CANopen 2 x RS485: Modbus RTU (of which 1 x RS485: also BACnet MS/TP) USB (type A); USB (type mini-B)	-
operating temperature	-20...+60°C	-

Electric and mount diagrams



AVD6200/C, AVC6200/C



AVD6200/C




AVC6200/C

Technical data

	AVD6200/C	AVC6200/C
size	4 DIN	
display	backlit LCD 128x64 pixel graphic display	-
power supply	24 Vac isolated 20...38 Vdc isolated	
digital outputs	6: 6 x 3 A 250 Vac	6: 6 x 3 A 250 Vac
analog outputs	2: 2 x 0-10 V, 2 x 0-10 V /4...20 mA / ON-OFF / PWM / O.C. 24 Vdc 50 mA max	
digital inputs	2 x SELV can operate as pulse/frequency counters up to 2 kHz	
analog inputs	8 x NTC C 103 AT / NTC NK103 / D.I. / PTC KTY81 / Pt1000 / 0...20 mA / 4...20 mA / 0-10 V / 0-5 V	
connectivity	CANBus: CANopen 2 x RS485: Modbus RTU (of which 1 x RS485: also BACnet MS/TP) USB (type mini-B); 1 x plug-in EVS: Ethernet: BACnet IP, Modbus TCP Master/Slave, Webserver, Ftp Client/Server, SNTP via specific EVS ETH plug-in module	
operating temperature	-20...+60 °C	


Electric and mount diagrams



AVD6200/C/L/U, AVD6200/C/L/U SSR, AVC6200/C/L/U



AVD6200/C/L/U



AVD6200/C/L/U SSR




AVC6200/C/L/U

Technical data

	AVD6200/C/L/U	AVD6200/C/L/U SSR	AVC6200/C/L/U
size		4 DIN	-
display	backlit LCD 128x64 pixel graphic display		-
power supply		24 Vac isolated 20...38 Vdc isolated	
digital outputs	6: 6 x 3 A 250 Vac	4: 4 x 3 A 250 Vac SSR: 2 x 0.2A 240 Vac	6: 6 x 3 A 250 Vac
analog outputs	2: 2 x 0-10 V, 2 x 0-10 V /4...20 mA / ON-OFF / PWM / O.C. 24 Vdc 50 mA max		
digital inputs		2 x SELV can operate as pulse/frequency counters up to 2 kHz	
analog inputs	12 x NTC 103 AT / NTC NK103 / D.I. / PTC KTY81 / Pt1000 / 0...20 mA / 4...20 mA / 0-10 V / 0-5 V		
connectivity	Ethernet: Bacnet IP, Modbus TCP Master/Slave, Webserver, Ftp Client/Server, SNTP CANBus: CANopen 2 x RS485: Modbus RTU (of which 1 x RS485: also BACnet MS/TP) USB (type A); USB (type mini-B); 1 x plug-in EVS		
operating temperature	-20...+60 °C	-20...+55 °C	-20...+60 °C

Electric and mount diagrams




AVD8400, AVD8400 SSR, AVC8400 /C /L /U (/I)models



AVD8400



AVD8400 SSR




AVC8400

Technical data

	AVD8400	AVD8400 SSR	AVC8400
size		8 DIN	
display		backlit LCD 128x64 pixel graphic display	
power supply		24 Vac (isolated, /I models only) 20...38 Vdc (isolated, /I models only)	
digital outputs	8: 7 x 3 A, 1 x 1A 250 Vac	6: 5 x 3 A, 1 x 1 A 250 Vac SSR: 2 x 0.5 A 240 Vac	8: 7 x 3 A, 1 x 1 A 250 Vac
analog outputs		4: 2 x 0-10 V, 2 x 0-10 V / 4...20 mA / ON-OFF / PWM / O.C. 24 Vdc 30 mA max	
digital inputs		6 x SELV 2 x pulse/frequency counters up to 2 kHz	
analog inputs		8 x NTC 103AT / NTC NK103 / D.I. / PTC KTY81 / Pt1000 / 0...20 mA / 4...20 mA / 0-10 V / 0-5 V	
connectivity		Ethernet: BACnet IP, Modbus TCP Master/Slave, Webserver, Ftp Client/Server, SNTP CANBus: CANopen 2 x RS485: Modbus RTU (of which 1 x RS485: also BACnet MS/TP) USB (type A); USB (type mini-B); 1 x plug-in EVS	
operating temperature		-20...+60 °C -20...+65 °C (/I models)	

Electric and mount diagrams




AVD8400 - AVD8400 SSR

AVC/AVD8400


AVD12600, AVD12600 SSR, AVC12600 /C /L /U (/I)models



AVD12600



AVD12600 SSR




AVC12600


Technical data

	AVD12600	AVD12600 SSR	AVC12600
size		8 DIN	
display		backlit LCD 128x64 pixel graphic display	
power supply		24 Vac (isolated, /I models only) 20...38 Vdc (isolated, /I models only)	
digital outputs	12: 10 x 3 A, 2 x 1 A 250 Vac	10: 8 x 3 A, 2 x 1 A 250 Vac SSR: 2 x 0.5A 240 Vac	12: 10 x 3 A, 2 x 1 A 250 Vac
analog outputs	6: 4 x 0-10 V, 2 x 0-10 V /4...20 mA / ON-OFF / PWM / O.C. 24 Vdc 30 mA max		
digital inputs		10 x SELV 2 x pulse/frequency counters up to 2 kHz	
analog inputs	12 x NTC 103 AT / NTC NK103 / D.I. / PTC KTY81 / Pt1000 / 0...20 mA / 4...20 mA / 0-10 V / 0-5 V		
connectivity		Ethernet: Bacnet IP, Modbus TCP Master/Slave, Webserver, Ftp Client/Server, SNTP CANBus: CANopen 2 x RS485: Modbus RTU (of which 1 x RS485: also BACnet MS/TP) USB (type A); USB (type mini-B); 1 x plug-in EVS	
operating temperature		-20...+60 °C -20...+65 °C (/I models)	


Electric and mount diagrams



AVD / AVC 8400, AVD / AVC 12600 /C/I models




AVD8400



AVC8400



AVD12600




AVC12600


Technical data

	AVC8400	AVD8400	AVC12600	AVD12600
size		8 DIN		
display	-	backlit LCD 128x64 pixel graphic display	-	backlit LCD 128x64 pixel graphic display
power supply		24 Vac isolated 20...38 Vdc isolated		
digital outputs	8: 7 x 3 A, 1 x 1A 250 Vac			12: 10 x 3 A, 2 x 1 A 250 Vac
analog outputs		6: 4 x 0-10 V, 2 x 0-10 V /4...20 mA / ON-OFF / PWM / O.C. 24 Vdc 30 mA max		
digital inputs			6 x SELV 2 x pulse/frequency counters up to 2 kHz	
analog inputs	8 x NTC 103AT / NTC NK103 / D.I. / PTC KTY81 / Pt1000 / 0...20 mA / 4...20 mA / 0-10 V / 0-5 V		12 x NTC 103 AT / NTC NK103 / D.I. / PTC KTY81 / Pt1000 / 0...20 mA / 4...20 mA / 0-10 V / 0-5 V	
connectivity		CANBus: CANopen 2 x RS485: Modbus RTU (of which 1 x RS485: also BACnet MS/TP) USB (type mini-B); 1 x plug-in EVS: Ethernet: BACnet IP, Modbus TCP Master/Slave, Webserver, Ftp Client/Server, SNTP via specific EVS ETH plug-in module		
operating temperature				-20...+65 °C

Electric and mount diagrams



AVD/AVC8400 /C/I



AVD/AVC12600 /C/I

FREE Evolution models



FREE Evolution

FREE Evolution models (**EVD** with display, **EVC** without display) are available in versions for assembly on 8 DIN rail, with disconnectable screw terminal blocks for quick, easy installation.

Every EVD or EVC is expandable via CANbus (field) up to 7 expansions and 2 terminals (EVK). Up to 10 controllers can also be connected together via CANbus (network).

Up to 127 devices can be controlled with Modbus Master, via RS485.

FREE Evolution with or without display /C indicates units with RTC – Real Time Clock; built-in RS485 and CANbus as standard

Model	Code	Relay outputs at hazardous voltage	SSR outputs	Analog outputs (SELV) A04/A05 configurable as Open Collector 12 Vdc 100 mA max each	Digital inputs at safety extra low voltage (SELV)	Digital inputs voltage free	Analog inputs at safety extra low voltage (SELV)
EVD7500/C/U	EVD7500060B00	7	-	5	8	1*	6
EVD75SS/C/U	EVD75SS060B00	5	2	5	8	1*	6
EVC7500/C/U	EVC7500060B00	7	-	5	8	1*	6

*Fast counter 1 kHz

** Also compatible with EVE4200 and EVE10200

Expansions RS485 (EVE7500 only) and built-in CANbus as standard

Model	Code	Relay outputs at hazardous voltage	SSR outputs	Analog outputs (SELV) A04/A05 configurable as Open Collector 12 Vdc 100 mA max each	Digital inputs at safety extra low voltage (SELV)	Digital inputs voltage free	Analog inputs at safety extra low voltage (SELV)
EVE7500	EVE7500000B00	7	-	5	8	1*	6
EVE4200	EVE4200000500	4	-	2	4	-	4

*Fast counter 1 kHz

Minimum developer kit - FREE Evolution

- FREE Studio Plus installation setup
- 1 FREE Evolution EVD7500/C/U
- USB cable
- FREE Evolution power supply transformer



Data download direction	→	←
Parameter map	✓	✓
IEC application	✓	✓
HMI application	✓	✓
Data files	✓	✓
BIOS	✓	-

Data download direction	→	←
Parameter map	-	-
IEC application	✓	✓
HMI application	✓	✓
Data files	✓	✓
BIOS	✓	-

Data download direction	→	←
Parameter map	✓	✓
IEC application	✓	-
HMI application	✓	-
Data files	✓	✓
BIOS	✓	-

EVD7500, EVD75SS, EVC7500



EVD7500



EVD75SS








EVC7500


Technical data

	EVD7500	EVD75SS	EVC7500
size		8 DIN	
display		backlit LCD 128x64 pixel graphic display	
power supply		24 Vac/dc - 48 Vdc isolated	
digital outputs	7: 2 x 8 A, 5 x 5 A 250 Vac -	5: 2 x 8 A, 3 x 5 A 250 Vac SSR: 2 x 1 A 250 Vac	7: 2 x 8 A, 5 x 5 A 250 Vac -
analog outputs		5 x 0-10 V / 4...20 mA (switch 0..20 mA) AO4/AO5 configurable as O.C. 12 Vdc 100 mA max each	
digital inputs		8 x SELV 1 x voltage free fast counter 1 kHz	
analog inputs		2 x NTC 103 AT / NTC NK103 / D.I. 4 x NTC 103 AT / NTC NK103 / D.I. / Pt1000 / 4...20 mA / 0-10 V / 0-5 V	
connectivity		USB; 1 x Plug-in EVS CANBus isolated: CANopen RS485 isolated: Modbus RTU	
operating temperature		-10...+55 °C	

Electric and mount diagrams



EVD7500 - EVD75SS



EVC7500

EVK1000 terminal






EVK1000


Technical data

EVK1000	
size	160x96x10 mm
mount	panel (for wall mount see Accessories page)
display	Backlit LCD
power supply	24 Vac/dc - 48 Vdc isolated
connectivity	CANbus isolated: CANopen
operating temperature	-5...+55 °C
code	EVK1000000B00

Electric, mount and dimensional diagrams



Expansions EVE7500, EVE4200



EVE7500






EVE4200


Technical data

	EVE7500	EVE4200
size	8 DIN	
mount	on DIN rail	
display	-	
power supply	24 Vac/dc - 48 Vdc isolated	24 Vac/dc
digital outputs	2 x 8 A 250 Vac 5 x 5 A 250 Vac	1: 1 x 5 A 250 Vac 3: 3 x 3 A 250 Vac
analog outputs	5 x 0-10 V / 4..20 mA /switch 0..20 mA	2 x 0-10 V
digital inputs	8 x SELV 1 x voltage free fast counter 1 kHz	4 x SELV
analog inputs	2 x NTC 103 AT / NTC NK103 / D.I. 4 x NTC 103 AT / NTC NK103 / D.I. / Pt1000 / 4...20 mA / 0-10 V / 0-5 V	4 x NTC 103AT / NTC NK103 / D.I. / Pt1000 / PTC / 4...20 mA / 0-10 V / 0-5 V -
connectivity	CANBus isolated: CANopen RS485 isolated: Modbus RTU 1 x EVS Plugin (only EVS RS485, EVS CAN)	CANBus: CANopen - -
operating temperature	-10...+55 °C	-5...+55 °C

Electric, mount and dimensional diagrams




EVE7500



EVE4200

Expansions EVE6000, EVE10200



EVE6000




EVE10200




Technical data

	EVE6000	EVE10200
size	4 DIN	
mount	on DIN rail	
power supply	24 Vac 20...38 Vdc	
digital outputs	6: 6 x 3 A 250 Vac -	10: 10 x 3 A 250 Vac -
analog outputs	-	2: 2 x 0-10 V, 2 x 0-10 V / 4...20 mA / ON-OFF / PWM / O.C. 24 Vdc 30 mA max
digital inputs	- 2 x pulse/frequency counters up to 2 kHz	4 x SELV 2 x pulse/frequency counters up to 2 kHz
analog inputs	4 x NTC 103 AT / NTC NK103 / D.I. / PTC KTY81 / Pt1000 / 0...20 mA / 4...20 mA / 0-10 V / 0-5 V	10 x NTC 103 AT / NTC NK103 / D.I. / PTC KTY81 / Pt1000 / 0...20 mA / 4...20 mA / 0-10 V / 0-5 V
connectivity	CANBus: CANopen	
operating temperature	-20...+65 °C	




Electric, mount and dimensional diagrams



EVE 6000



EVE6000 / EVE10200



EVE6000 / EVE10200

Plugin EVS



Technical data


EVS	
size	2 DIN
mount	on DIN rail
power supply	from base EVD/EVC/AVD

Connectivity



Model	Code	Hazardous voltage output	Connectivity protocol	Compatibility
EVS RS232	EVS10R2000000	1 x SPDT 5A 250 Vac	Modbus ASCII	FREE Advance - FREE Evolution
EVS RS485	EVS00R4000000	-	Modbus RTU	FREE Advance - FREE Evolution
EVS CAN	EVS00CA000000	-	CANopen	FREE Advance - FREE Evolution
EVS Bacnet	EVS00BM000000	-	Modbus RTU - BACnet MSTP	FREE Advance - FREE Evolution
EVS LONWORKS	EVS0LON000000	-	LON	FREE Advance - FREE Evolution
EVS ETH	EVS00ET000000	-	Modbus TCP - BACnet IP - WebServer	FREE Advance / C/I - FREE Evolution
EVS Profibus	EVS00PB000000	-	Profibus DP Slave-V0	FREE Evolution
EVS ETH/RS485	EVS00EB000000	-	Modbus RTU - BACnet MSTP - Modbus TCP - BACnet IP - Webserver	FREE Evolution

Electric, mount and dimensional diagrams


EVS ETHERNET





EVS LON




EVS CAN




EVS RS232/R



EVS RS485 BACnet MS/TP



EVS RS485



Accessories

In association with FREE Smart, FREE Panel, FREE Evolution and FREE Advance, Eliwell supplies a vast range of accessories, from a protected transformer to IP68 temperature probes, ratiometric pressure transducers and pressure switches.

Single-phase (with currents from 2 to 9A) and three-phase fan modules are available.

No additional serial interfaces are required for connection of ratiometric pressure probes, external modules (such as fan modules) or terminals.

FREE Smart accessories

Converters, interfaces, programming keys

Code	Description	Details
SAR0RA00X701	USB/485 MINI KIT converter	-
DMI1003002000	DMI100-3 Manufacturer interface module	For FREE Smart only
MFK100T000000	MFK: programming key for parameter, application upload/download	For FREE Smart only

Wiring

Code	Description	Details
COLV0000E0100	I/O connection wiring - safety extra low voltage (SELV) - 1 m cable	FREE Smart 12...24V only
COLV000035100	RS485 Wiring	FREE Smart 12...24V only
COLV000042100	Wiring AO3-4-5 - 1 m cable	FREE Smart 12...24V only

Connectivity

Code	Description	Details
BA10000R3700	BusAdapter 150 TTL-RS485	For FREE Smart only

Humidity module

Code	Description	Details
KP100000	Humidity module %RH	For SKW terminal

Demo Case

Code	Description	Details
VAL00031K	Demo Case for FREE Smart	-

Temperature probes*

Code	Description	Details
SN8DED11502C0	NTC 103AT 5X20 1.5 mt TPE IP68	-
SN8DAE11502C0	NTC 103AT 6X20 1.5 mt TPE IP68	-
SN9DAE11502C6	Pt1000 6X20 1.5 mt IP68	FREE Smart 4500
SN9DED11502C6	Pt1000 5X20 1.5 mt IP68	

Transformers

Code	Description	Details
TF411205	Transformer 230 Vac/12 V 6 VA (protected)	For FREE Smart only
TF411210	Transformer 230 Vac/12 V 11 VA (protected)	For FREE Smart only
TF111211	Transformer 220 Vac/24 V-24 V 16 VA	For FREE Smart only

KEY: SELV = Safety Extra Low Voltage

*different cable lengths available on request

FREE Advance, FREE Evolution and FREE Panel accessories

Converters, interfaces, programming keys

Code	Description	Details
SAR0RA00X701	USB/485 MINI KIT converter	-
EVA00USCA0000	USB/CAN converter	-

Base plates

Code	Description	Details
EVA00WMRC0000	Kit (4 Pcs) White base plate for wall mount	For EVP/EVK
EVA00WMRC0001	Kit (4 Pcs) Black base plate for wall mount	For EVP/EVK
AVA00WMRC0000	White base plate for wall mount	For AVP1000
AVA00WMRC0001	Grey base plate for wall mount	For AVP1000

Demo Case

Code	Description	Details
VAL00033K	Demo Case for FREE Evolution	-
VAL00034	Demo Case for FREE Advance	-

Temperature probes*

Code	Description	Details
SN8DED11502C0	NTC 103 AT 5X20 1.5 m TP IP68	-
SN8DAE11502C0	NTC 103 AT 6X20 1.5 m TP IP68	-
SN9DAE11502C6	Pt1000 6X20 1.5 m IP68	FREE Evolution / FREE Advance
SN9DED11502C6	Pt1000 5X20 1.5 m IP68	FREE Evolution / FREE Advance

Transformers

Code	Description	Details
TF111202	Transformer 230V~/24 V 25 VA	For FREE Evolution only
TF111205	Transformer 230V~/24 V 35 VA DIN rail mount	FREE Evolution / FREE Advance

FREE range accessories

Pressure transducers

Code	Description	Details
TD220050	EWPA050 4...20 mA / 0...667 psi / 0..50 bar IP54** 2 m cable	1/4 SAE MALE
TD220007	EWPA007 4...20 mA / -7...101.5 psi / -0.5..7 bar IP54** 2 m cable	1/4 SAE MALE
TD320050	EWPA050 4...20 mA / 0...667 psi / 0..50 bar IP54** 2 m cable	1/4 SAE FEMALE
TD320007	EWPA007 4...20 mA / -7...101.5 psi / -0.5..7 bar IP54** 2 m cable	1/4 SAE FEMALE

Ratiometric transducers

Code	Description	Details
TD420010	EWPA 010 R 0...145 psi / 0...10 bar IP67 2 m cable (packard connector)	Female connection
TD420030	EWPA 030 R 0...508 psi / 0...30 bar IP67 2 m cable (packard connector)	Female connection
TD420050	EWPA 050 R 0...667 psi / 0...50 bar IP67 2 m cable (packard connector)	Female connection

Expansions, fan modules

Code	Description	Details
MW320100	EXP11 250 V 10 A expansion with DIN rail mount base	Open Collector Output
MW991012	CFS05 TANDEM TRIAC 5+5 A 250 V	-
CFS Modules	CFS - Single-phase speed regulators for currents from 2 A to 9 A	Various articles available

KEY: SELV = Safety Extra Low Voltage

*different cable lengths available on request **optional IP67 version with packard connector

A photograph of a person's hand pointing their index finger towards a world map displayed on a screen. The screen has a dark background with a grid overlay and some blurred text or binary code visible. A white rectangular box highlights the world map. The overall composition suggests a presentation or a user interface demonstration.

Life Is On



ITALY - HEADQUARTERS

Eliwell Controls Srl

Via dell'Industria, 15 Z. I. Paludi

32016 Alpago (BL) Italy

T +39 0437 986 111

Sales

T +39 0437 986 100 (Italy)

T +39 0437 986 200 (other countries)

E: saleseliwell@schneider-electric.com

Technical support

T +39 0437 986 250

E: eliwell.freeway@schneider-electric.com



Contact us



Follow us on

CT123390 • rel. 10/18
© 2018 Eliwell - All rights reserved

Eliwell has been delivering control systems and services for commercial and industrial refrigeration and air-conditioning units for more than 35 years, with ground-breaking products packed with state-of-the-art technology. Eliwell is a company of the Schneider Electric Group. Subscribe to our newsletter on the www.elowell.com website.